

Document	RY-TDS-801
Revision	Rev. 1.0
Issue date	July 2026
Status	Issued

[object Object]

[object Object] · [object Object]

1. PRODUCT DESCRIPTION

Rayson GripSafe AP12 is a one-pack, self-crosslinking acrylic primer filler loaded with 0.5–1.5 mm silicate quartz aggregate that builds an anti-slip texture directly onto concrete and asphalt.

GripSafe AP12 puts the anti-slip aggregate in the can. Instead of broadcasting loose grit into a wet primer, the 0.5–1.5 mm silicate quartz is factory-blended into a self-crosslinking acrylic binder — so every pass lays down a consistent, repeatable texture. It doubles as primer and filler, keying subsequent finish coats.

2. RECOMMENDED USES

- Pedestrian walkways and ramps
- Industrial floors requiring slip resistance
- Playgrounds, basketball courts and tennis courts
- Cycling pathways

4. KEY PROPERTIES

- Factory-blended 0.5–1.5 mm quartz gives consistent anti-slip texture
- One pack, ready to use — no broadcasting step
- Fast-drying with high abrasion and excellent water resistance
- Non-yellowing, interior and exterior; VOC under 50 g/litre
- anti slip
- abrasion resistance
- uv stability

3. SUITABLE SUBSTRATES

- Grey concrete
- Asphalt surfaces
- Hard surfaces such as stone
- Unglazed tiles and pavers

5. SYSTEM ROLE

primer.



Figure 1 — Typical system build-up (top to bottom). Layer thicknesses are system-dependent; confirm the specification for your project.

6. TECHNICAL DATA

Surface preparation	[object Object]
Mixing / dilution	[object Object]
Application method	Trowel or squeegee, Brush for stripe-coating edges
Coverage	[object Object]
Application conditions	[object Object]
Drying & curing	[object Object]
Recoat interval	[object Object]
Film / thickness	[object Object]
Pack sizes	[object Object]

Storage	[object Object]
Shelf life	[object Object]

7. APPLICATION WORKFLOW



Figure 2 — Application workflow. Each stage is a hold point: confirm the previous stage is complete and within specification before proceeding.

8. RECOMMENDED SYSTEM

Anti-slip walkway or ramp

- 1. Clean, repair and level the surface; stripe-coat edges by brush
- 2. Apply Rayson GripSafe AP12 across the area; overcoat dull patches with a further coat
- 3. Finish with Rayson UraForce HY15 or CourtFlex AC25 in the selected colour

9. LIMITATIONS

- Ambient and surface temperature above 10 °C, and at least 5 °C above the dew point
- Surface must be dry, clean and free of loose paint, dust, grease, oil, wax and biological growth
- Neutral colour only — pair with a coloured finish coat where colour is required
- Texture grade is fixed by the factory aggregate blend

10. HEALTH & SAFETY

[object Object]

DISCLAIMER

The information in this data sheet is given in good faith and reflects typical values and general good practice. Because site conditions and workmanship are beyond our control, Rayson gives no warranty implied from this document; users should verify suitability for their specific application and confirm they are working from the current issue. For project-specific advice, contact the Rayson technical team.

RAYSON HIGH PERFORMANCE COATINGS

Singapore
Tel / WhatsApp: +65 9821 9129
samuelpacx@hotmail.com

Product page:
<https://rayson.sparcoasia.com/products/gripsafe-ap12/>